

APPLICATOR'S GUIDE

SILACAST PCS

PENETRATING CLEAR SEALER

Always perform a jobsite test prior to applying Silacast PCS to ensure desired results.

LIMITATIONS:

Silacast PCS should not be applied to glass, glazed tile, painted or previously sealed materials. Avoid drips and runs and do not over apply product. Do not interrupt application process until area is completely treated. Silacast PCS is 100% water based and cannot be reapplied to itself. If product is over applied a whitening will appear on the substrate leaving undesired results.

Silacast PCS should be applied in temperatures between 38 degrees Fahrenheit and 90 degrees Fahrenheit. It is recommended in higher temperatures and in direct sunlight to mist the substrate with water prior to applying Silacast PCS to break the surface tension. This will allow Silacast PCS to dry slower and penetrate deeper in to the material. This will also reduce the chance of the product whitening.

Silacast PCS will not stop water from entering through cracks or holes in the material.

Proper safety concerns should be followed when using any sealers. Gloves and eye protection are recommended. Always keep a MSDS on hand.

There are several different ways to apply this product depending on the budget and size of the job

One or two gallon garden pump sprayer

Back pack pump sprayer

Four gallon pressure tank

18- 25 gallon electric tank sprayer



Light Duty



Light/
Medium Duty



Large Duty



Heavy Duty

APPLICATION:

Inspect surface to be treated. Clean off any dirt oils or other foreign objects that could prevent Silacast PCS from penetrating the material. Apply Silacast PCS without dilution with desired equipment. Apply until saturated. Do not interrupt application process until area is completely treated. Cover all surfaces not to be treated. Do not get on glass.

Do not apply when threat of rain is imminent. Use caution on windy days to prevent over spray from contacting other surfaces.

If there is any question or concerns about application of Silacast PCS contact your representative.

Silacast PCS should be installed by a trained/ skilled applicator to ensure accurate installation. Deco Products warrants its product to be manufactured with the highest quality but cannot guaranty its performance when installed improperly.